

# **Network Camera Firmware**

Version: V5.4.5 Release Note

(2017-02-08)

Firmware  Basic Information	Firmware Version:	V5.4.5 170208
	SDK Version:	V5.2.6.25
	Play Library (PlayCtrl.dll)	V7.3.0.74
	Encapsulation Library (SystemTransform.dll)	V2.5.1.14
	RTSP Communication Library (StreamTransClient.dll)	V1.1.3.6
	Smart configuration library	V4.1.8.1
	iVMS-4200	Version 4200 V2.05.05.13 build20170119
	IE Client version	V3.0.6.1 build170117

### **Hikvision Firmware V5.4.5 Features**

## \*for 1X01 Network Cameras (V5.4.5 build170208)

- 1. New Features
- New models available: DS-2CD1001-I and DS-2CD1301-I(C).
- HiDDNS and IPServer are no longer supported
- Support Hik-Connect service, with Hik-Connect dynamic Domain Name service and alarm push service.
- LBS address for Hik-Connect function is dev.hik-connect.com. Neutral version is called
   Guarding vision and LBS address is dev.guardingvision.com.
- Hik-Connect function is disabled as default.
- <u>Verification code is removed from device label and verification code information is removed</u> from QR code.
- During device activation or enabling Hik-Connect function for the first time, verification code
   should be created or changed by customers. (Rules: 6 to 12 letters (a to z, A to Z) or numbers



### (0 to 9), Case Sensitive.)

Open Source Software Licenses is displayed on web browser ->System->System
 Settings->About Device.

## 2. Improved Features

- Hik-Connect Alarm push service is independent to motion detection video recording.
- Admin account user is able to enable/disable Hik-Connect service. Admin account user is able

to view verification code for Hik-Connect service on web browser or iVMS-4200.

- In login web interface, password can be seen.
- Time zones of particular areas are updated: Istanbul is changed to GMT+3:00 and Novosibirsk

is changed to GMT+7:00.

• In DST configuration of French web page, the typo of Tuesday and Thursday is corrected.

## **Compatibility Update**

### • NUUO:

1. Version: V6.9.0, drive version: V5.2;

2. Protocol: HIKCGI

### Milestone:

- 1. Milestone Enterprise 8.1a(10.1a), Milestone drive version (Driver 8.8), test HIKCGI
- 2. Milestone software version (Milestone Corporate 10.2a), Milestone drive version (Driver 8.8), test HIKCGI

#### • Avigilon:

1. Control Center: V5.10.4.6;

2. Test ONVIF.

#### • Excaqvision:

Version: 8.2.1.107318
 Protocol: HIKCGI, ONVIF

#### ONVIF

Tool version 1601

#### Tested NVR

E Series: DS-96128N-E16(V3.0.4\_150616)(Discontinued, no longer tested in future versions)

F Series: DS-96128N-F16(V3.2.6 160411) E Series: DS-7732N-E4/16P(V3.4.91)



G Series: DS-7608N-G2/4P(V3.4.1 build 151225)

K1 Series: DS-7816N-K1(V3.4.90)

I8 Series: DS-8664N-I8, DS-7632N-I2/16P

K Series: V3.4.91

DS-7608N-SHT(V3.0.17\_150804)

DVR: DS-9016HF-ST(V3.4.3) DS-7616N-SE(V3.0.15\_150528)

F Series:DS-9664N-F8/I(V3.3.4\_150715)

DS-7832N-K2(V3.3.9\_151228) 96000N-I Series NVR(3.6.0)

## **Customer Impact and Recommended Action**

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

#### **Remarks:**

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.

No. 555 Qianmo Road, Binjiang District, Hangzhou 310051, China

Tel: +86-571-8807-5998 FAX: +86-571-8993-5635

Email: overseabusiness@hikvision.com

Supported Product List (1X01)			
Product Category	Model Number	Product Description	
Mini IR Bullet	DS-2CD1001-I	1MP, IR	
Mini IR Dome	DS-2CD1101-I	1MP, IR	
Mini EXIR Turret	DS-2CD1301-I(C)	1MP, IR	