

Network Camera-V5.7.0 Release Note-H8 (2022-07-20)

Firmware Basic Information Firmware version: V5.7.0 build220720

New Features

- 1. New products: 3 series medium telephoto products. The main stream supports 1080 high frame rate (only supported in monitoring mode). Smart event support Intrusion Detection, Line Crossing Detection, Region Entrance/Exiting Detection, 5 ROI areas, does not support rotation.
- 2. Default open Center Mirror because the lens is installed in reverse.
- 3. Image Scene default outdoor. Image configuration style reference PT camera.

Modify Function

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action.

For any questions and request for this firmware, please contact our local technical support team.

Remarks:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.



Hikvision Digital Technology CO., Ltd.

No. 555 Qianmo Road, Binjiang District, Hangzhou 310051,

China

Tel: +86-571-8807-5998 FAX: +86-571-8993-5635

Email: overseabusiness@hikvision.com

Supported Product List	
Product Category	Model Number
3 Series	DS-2CD3A26G2T-IZS