

Network Camera Firmware

Version: V5.4.5

Release Note (2017-01-24)

Firmware Basic Information	Firmware Version:	V5.4.5
	SDK Version:	V7.3.2.74
	Play Library (PlayCtrl.dll)	V7.3.0.74
	Encapsulation Library (SystemTransform.dll)	V2.5.1.14
	RTSP Communication Library (StreamTransClient.dll)	V1.1.3.6
	Voice intercom library (AudioIntercom.dll)	V1.4.0.1
	iVMS-4200	Version 4200 V2.5.5.103 build20170119
	IE Client version	V3.0.6.1 build170117

Hikvision Firmware V5.4.5 Features

**for all IPC platforms*

1. New Features

- HiDDNS and IP Server are no longer supported
- Add Hik-Connect function, support Hik-Connect Domain Name and alarm push service.
- LBS address for Hik-Connect function is dev.hik-connect.com.
- Hik-Connect function is disabled as default.
- Verification code is removed from device label and verification code information is removed from QR code.
- During device activation or enabling Hik-Connect function for the first time, verification code should be created or changed by customers. (Rules: 6 to 12 letters (a to z, A to Z) or numbers (0 to 9), Case Sensitive.)

- Add Open Source Software Licenses on web browser ->System->System Settings->>About Device.

2. Improved Features

- Admin account user is able to enable/disable Hik-Connect service. Admin account user is able to view verification code for Hik-Connect service on web browser or iVMS-4200.
 - Time zones of particular areas are updated: Istanbul is changed to GMT+3:00 and Novosibirsk is changed to GMT+7:00.
 - In DST configuration of French web page, the typo of Tuesday and Thursday is corrected. ●
 - Intrusion detection and line crossing detection alarm types are available on Hik-Connect service.
- Note:** Intrusion detection and line crossing detection rules should be configured on web browser, iVMS client or NVR after enabling Alarm Notification on Hik-Connect APP.

**for 2XX2 Network Cameras (V5.4.5 build170123)*

- The Day/Night mode switches based on the result of image algorithm rather than photoresistance.

**for 2XX0 Network Cameras (V5.4.5 build170123)*

- The Day/Night mode switches based on the result of image algorithm rather than photoresistance.
- Remove HiDDNS and IPServer.
- Add Hik-Connect function, support Hik-Connect Domain Name and alarm push service.
- LBS address for Hik-Connect function is change to dev.hik-connect.com.
- Hik-Connect function is disabled as default.
- Verification code is removed from device label and verification code information is removed from QR code.
- During device activation or enabling Hik-Connect function for the first time, verification code need to be created or changed by customers. (Rules: 6 to 12 letters (a to z, A to Z) or numbers (0 to 9), Case Sensitive.)

- Add Open Source Software Licenses on web browser ->System -> System Settings -> About Device.
- SVC is no longer support

****for 2XX2(F)WD, 2X52, 64X4 Network Cameras (V5.4.5 build170124)***

- Live view performance of DS-2CD6424FWD-10/20/30 is improved.
- When WDR is on, black image would not occur to DS-2CD6414FWD-10/20/30.
- Single object would not trigger multiple line crossing or intrusion alarms on iVMS-4200.

****for 4X26FWD ANPR Network Cameras (V5.4.5 build170123)***

- The firmware is only applied to the specified models with /P.
- Supported below regions of integrating Hikvision LPR library : Italy, Netherlands, England, Ireland,
Germany, France, Singapore, Malaysia, Indonesia, Australia, Vietnam, Philippines, HongKong,
Macao, Taiwan, Brazil, Ecuador, Columbia, Chile, Peru, South Africa, Turkey.
- Newly added 2 options of license plate recognition mode: "City Street" and "Alarm Input". ●
Newly support the mode of "Alarm Input" in the License Plate Settings to trigger the license plate recognition and capture.
- Support to set the size of license plate which ranges from 64 to 2048kb.
- Modify the interface of Arming Schedule and Linkage Method. It is necessary to match the direction for linkage.
- 5200 will trigger the LPR library to capture the license plate and upload the result by SDK.
- Support to export vehicle information including License Plate Number, Capture Time, Country, Lane, Direction and Validity with excel format in the live view browser.
- Support to upload and display the vehicle recognition direction which includes Forward and Reverse in real-time.
- Support to upload and display the validity.
- Support FTP uploading pictures and editing the names. It can choose the Default or Custom mode when naming the pictures. The length of name should be within 95 characters.

- Support to display the license plate information in real-time.
- Support to export the Blacklist & Whitelist.
- Remove the Smart Event.
- Support barrier gate controlling SDK in IVMS-5200.
- Support ANR function for vehicle information.
- Support the non-photoresistance day and night switch.
- Normal and Road scenarios are optional and they use different image parameters for image configuration.
- ISAPI and ONVIF support to upload the ID information of lanes and small image of license plate.
- Newly support to search the pictures via Plate No.
- For DS-2CD4A26FWD-LZS/P, it can realize the timed switch of fill light.

Compatibility Update

- ONVIF version: V2.4, official test tool version: V1601;
- NUUO:
 1. Version: V6.9.0, drive version: V5.2;
 2. Protocol: HIKCGI ● Milestone:
 1. Milestone Enterprise 8.1a(10.1a), Milestone Corporate 10.2a
 2. Milestone drive version : Device Pack 8.8 ● Avigilon:
 1. Control Center: V5.10.4.6;
 2. Test ONVIF.
- Excaqvision:
 1. Version: 7.2.3
 2. Protocol: HIKCGI, ONVIF ● Genetec Omnicast:
Version: 4.8 SR8 ●

Security Center:

Version: 5.5 SR3

- Network Keyboard:

DS-1100K V2.4.0 build150827 ●

Series port keyboard:

DS-1004K V1.2.0

- **Tested NVR/DVR accessing:**

1. E series: DS-96128N-E16 (V3.0.4_150616) (This series NVRs has been discontinued and the future version will not test)
2. F series: DS-96128N-F16 (V3.2.6 160411)
3. E series: DS-7732N-E4/16P (V3.4.91)
4. G series: DS-7608N-G2/4P (V3.4.1 build 151225)
5. K1 series: DS-7816N-K1 (V3.4.90)
6. I8 series: DS-8664N-I8 (DS-7632N-I2/16P)
7. K series: V3.4.91
8. DS-7608N-SHT (V3.0.17_150804)
9. Netra DVR: DS-9016HF-ST (V3.4.3)
10. DS-7616N-SE (V3.0.15_150528)
11. F series: DS-9664N-F8/I (V3.3.4_150715)
12. Channel NVR: DS-7832N-K2 (V3.3.9_151228)
13. 96000N-I series: V3.6.0

Customer Impact and Recommended Action

This update refers to function/compatibility improvement and will take effect automatically after the Date of Change. We are very sorry for any inconvenience of use-habit changes caused by this action. For any questions and request for this firmware, please contact our local technical support team.

Remarks:

- Hikvision reserves the right to change, alter or withdraw the above notification without prior notice.
- Product design and specifications are subject to change without prior notice.
- The Hikvision firmware may contain defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.
- Hikvision is not liable for any typing or printing errors.

Hikvision Digital Technology CO., Ltd.

No. 555 Qianmo Road, Binjiang District, Hangzhou 310051, China

Tel: +86-571-8807-5998

FAX: +86-571-8993-5635

Email: overseabusiness@hikvision.com

Supported Product List (2XX2)

Product Category	Model Number	Product Description
Mini IR Bullet	DS-2CD2012-I	1.3MP, IR
Mini IR Bullet	DS-2CD2022-I	2MP, IR
Mini IR Bullet	DS-2CD2032-I	3MP, IR
Mini IR Bullet	DS-2CD2012F-I(W)	1.3MP, IR, Wi-Fi
Mini IR Bullet	DS-2CD2022F-I(W)	2MP, IR, Wi-Fi
Mini IR Bullet	DS-2CD2032F-I(W)	3MP, IR, Wi-Fi
IR Fixed Dome	DS-2CD2112F-I(S)(W)	1.3MP, IR
IR Fixed Dome	DS-2CD2122F-I(S)(W)	2MP, IR
IR Fixed Dome	DS-2CD2132F-I(S)(W)	3MP, IR
EXIR Turret	DS-2CD2312-I	1.3MP, up to 30m IR
EXIR Turret	DS-2CD2332-I	3MP, up to 30m IR
IR Cube	DS-2CD2412F-I(W)	1.3MP, IR, Wi-Fi optional

IR Cube	DS-2CD2432F-I(W)	3MP, IR, Wi-Fi optional
IR Mini Dome	DS-2CD2512F-I(S)	1.3MP, IR, Audio/Alarm optional
IR Mini Dome	DS-2CD2532F-I(S)	3MP, IR, Audio/Alarm optional
VF IR Bullet	DS-2CD2612F-I(S)	1.3MP, VF lens, IR, Audio/Alarm optional
VF IR Bullet	DS-2CD2622F-I(S)	2MP, VF lens, IR, Audio/Alarm optional
VF IR Bullet	DS-2CD2632F-I(S)	3MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2712F-I(S)	1.3MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2722F-I(S)	2MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2732F-I(S)	3MP, VF lens, IR, Audio/Alarm optional
EXIR Bullet	DS-2CD2T12-I3/I5/I8	1.3MP
EXIR Bullet	DS-2CD2T22-I3/I5/I8	2MP
EXIR Bullet	DS-2CD2T32-I3/I5/I8	3MP

Supported Product List (XXX0)

Product Category	Model Number	Product Description
Mini IR Bullet	DS-2CD2010-I	1.3MP, IR
Mini IR Bullet	DS-2CD2010F-I(W)	1.3MP, IR, Wi-Fi
Mini IR Bullet	DS-2CD2020-I	2MP, IR
Mini IR Bullet	DS-2CD2020F-I(W)	2MP, IR, Wi-Fi
IR Fixed Dome	DS-2CD2110F-I(W)(S)	1.3MP, IR
IR Fixed Dome	DS-2CD2120F-I(W)(S)	2MP, IR
IR Cube	DS-2CD2410F-I(W)	1MP, IR, Wi-Fi optional

IR Cube	DS-2CD2420F-I(W)	2MP, IR, Wi-Fi optional
Mini Dome	DS-2CD2510F	1.3MP
Mini Dome	DS-2CD2520F	2MP
VF IR Bullet	DS-2CD2610F-I(Z)(S)	1.3MP, VF lens, IR, Audio/Alarm optional
VF IR Bullet	DS-2CD2620F-I(Z)(S)	2MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2710F-I(Z)(S)	1.3MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2720F-I(Z)(S)	2MP, VF lens, IR, Audio/Alarm optional
Box Camera	DS-2CD2810F	1.3MP, box camera
Box Camera	DS-2CD2820F	2MP, box camera
EXIR Bullet	DS-2CD2T10-I3/I5/I8	1.3MP, EXIR Bullet
EXIR Bullet	DS-2CD2T20-I3/I5/I8	2MP, EXIR Bullet
IR Mini PT	DS-2CD2Q10FD-IW	1MP, Wi-Fi
Pinhole	DS-2CD2D14WD	1MP
IR Dome	DS-2CD6510-I(O)	1.3MP, IR, Audio/Alarm optional

Supported Product List (1X31, 1X41, 2XX2(F)WD, 2X52, 64X4)

Product Category	Model Number	Product Description
Mini IR Bullet	DS-2CD2022WD-I	2MP, IR, WDR
Mini IR Bullet	DS-2CD2042WD-I	4MP, IR, WDR
Mini IR Bullet	DS-2CD2052-I	5MP, IR
IR Fixed Dome	DS-2CD2122FWD-I(W)(S)	2MP, IR, Wi-Fi, WDR

IR Fixed Dome	DS-2CD2142FWD-I(W)(S)	4MP, IR, Wi-Fi, WDR
IR Fixed Dome	DS-2CD2152F-I(W)(S)	5MP, IR, Wi-Fi
EXIR Turret	DS-2CD2322WD-I	2MP, IR, WDR
EXIR Turret	DS-2CD2342WD-I	4MP, IR, WDR
EXIR Turret	DS-2CD2352-I	5MP, IR
IR Cube	DS-2CD2422FWD-IW	2MP, IR, WDR
IR Cube	DS-2CD2442FWD-IW	4MP, IR, WDR
IR Cube	DS-2CD2452F-IW	5MP, IR
IR Mini Dome	DS-2CD2522FWD-(I)(W)(S)	2MP, IR, WDR, Wi-Fi/Audio/Alarm optional
IR Mini Dome	DS-2CD2542FWD-I(W)	4MP, IR, WDR, Wi-Fi optional
IR Mini Dome	DS-2CD2552FWD-I(W)	5MP, IR, Wi-Fi optional
VF IR Bullet	DS-2CD2622FWD-I(Z)(S)	2MP, VF lens, IR, Audio/Alarm optional
VF IR Bullet	DS-2CD2642FWD-I(Z)(S)	4MP, VF lens, IR, Audio/Alarm optional
VF IR Bullet	DS-2CD2652F(D)-I(Z)(S)	5MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2722FWD-I(Z)(S)	2MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2742FWD-I(Z)(S)	4MP, VF lens, IR, Audio/Alarm optional
VF IR Dome	DS-2CD2752F-I(Z)(S)	5MP, VF lens, IR, Audio/Alarm optional
EXIR Bullet	DS-2CD2T22WD-I3/I5/I8	2MP, IR, WDR
EXIR Bullet	DS-2CD2T42WD-I3/I5/I8	4MP, IR, WDR
EXIR Bullet	DS-2CD2T52-I3/I5/I8	5MP, IR
PT Dome	DS-2CD2F12FWD-I(W)(S)Z	1.3MP, IR, WDR, PT, VF lens
PT Dome	DS-2CD2F22FWD-I(W)(S)	2MP, IR, WDR, PT, WiFi/Audio/Alarm optional
PT Dome	DS-2CD2F42FWD-I(W)(S)	4MP, IR, WDR, PT, WiFi/Audio/Alarm optional
PT Dome	DS-2CD2F52F-I(W)(S)	5MP, IR, PT, WiFi/Audio/Alarm optional
Separated	DS-2CD6414FWD(-10,-20,-30)	1.3MP
Separated	DS-2CD6424FWD(-10、-20、-30)	2MP
Mobile	DS-2XM6612DFWD-I	1.3MP
Mobile	DS-2XM6622DFWD-I	2MP

Supported Product List (4X26FWD/P)

Product Category	Model Number	Product Description
Box Camera with housing	DS-2CD4026FWD/P-IRA(11-40mm)	2MP, WDR, IR
Box Camera with housing	DS-2CD4026FWD/P-INRA(11-40mm)	2MP, WDR, IR
Box Camera with housing	DS-2CD4026FWD/P-HIRA(11-40mm)	2MP, WDR, IR, Heater
Box Camera with housing	DS-2CD4026FWD/P-IR5(3.8-16mm)	2MP, WDR, IR
Box Camera with housing	DS-2CD4026FWD/P-L(7-33mm)	2MP, WDR,LED light
Box Camera with housing	DS-2CD4026FWD/P-L(11-40mm)	2MP, WDR,LED light
Box Camera with housing	DS-2CD4026FWD/P-L(3.8-16mm)	2MP, WDR,LED light
IR Bullet	DS-2CD4A26FWD-IZ/P(2.8-12mm)	2MP, WDR, IR, Motorized VF lens
IR Bullet	DS-2CD4A26FWD-IZ/P(8-32mm)	2MP, WDR, IR, Motorized VF lens
IR Bullet	DS-2CD4A26FWD-IZS/P(2.8-12mm)	2MP, WDR, IR, Motorized VF lens
IR Bullet	DS-2CD4A26FWD-IZS/P(8-32mm)	2MP, WDR, IR, Motorized VF lens
IR Bullet	DS-2CD4A26FWD-IZHS/P(2.8-12mm)	2MP, WDR, IR, Motorized VF lens, Heater
IR Bullet	DS-2CD4A26FWD-IZHS/P(8-32mm)	2MP, WDR, IR, Motorized VF lens, Heater
Bullet with LED light	DS-2CD4A26FWD-LZS/P(2.8-12mm)	2MP, WDR, IR, Motorized VF lens, LED light
Bullet with LED light	DS-2CD4A26FWD-LZS/P(8-32mm)	2MP, WDR, IR, Motorized VF lens, LED light
IR Bullet	DS-2CD4626FWD-IZ/P(2.8-12mm)	2MP, WDR, IR, Motorized VF lens
IR Bullet	DS-2CD4626FWD-IZHS/P(2.8-12mm)	2MP, WDR, IR, Motorized VF lens, Heater